T11

PRIMARY SERIES




HANSA
PRECISION EQUIPMENT

T11 PRIMARY SERIES


The T11 combines a high-capacity bin with an impressive 36m spread pattern and iconic Hansa longevity. Designed for efficient bulk work, it delivers maximum cost efficiency by omitting Pro Series add-ons like boundary control and hydraulic drawbar suspension.





VARIABLE RATE TECHNOLOGY

Seamlessly maximise input efficiency using the Hansa H7 variable rate controller. Set your desired application rate, bout width and spinner speed directly from the cab, allowing precise rate control without the guesswork.



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T11 is built for ultimate durability. A grit blasted and 2 pack painted chassis protects against corrosion, ensuring long-term structural integrity and a premium finish.



UPGRADED HYDRAULIC MOTORS

Heavy-duty hydraulic motors deliver high-flow power to maintain precise application rates at faster ground speeds. This ensures consistent coverage, maximises field efficiency, and reduces operating time without sacrificing accuracy.

Inclusions & Options

Inclusions ●
Optional ○

TYRES	Range of Tractor and Floatation tyre options available. Contact your local Hansa Dealer for a full list.	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	○ ○
AXLE	Single Series 150 ADR 10/335 (track options of 1,400mm - 3,000mm)	●
BIN CONSTRUCTION	2B 304 grade stainless steel	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

SPREAD WIDTH
36m Urea, 18m Lime

VOLUME (WATER LEVEL)
8,500L

VOLUME (FERTILISER)
9,400L

VOLUME (LIME)
11,000L

TARE WEIGHT
2,850kg

UREA CAPACITY
7,050kg

LIME CAPACITY
11,000kg

LOADING HEIGHT
2,600mm

BIN LENGTH
3,800mm

OVERALL LENGTH
6,980mm

BIN WIDTH
2,300mm

AXLE TRACK
1,400mm - 3,000mm
(Depending on tyre size)

CONVEYOR WIDTH
725mm wide

CARRYING CAPACITY
11,000kg

OIL FLOW
115L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

HANSA PRECISION EQUIPMENT