T14

PRO SERIES




HANSA
PRECISION EQUIPMENT

T14 PRO SERIES


Designed around your needs on the job, the Hansa T14 in the Pro Series comes fully equipped from day one. By including essential features as standard, it delivers maximum functionality, giving you complete performance and total reliability without the additional cost of extra add-ons.






STANDARD BOUNDARY CONTROL

Precision boundary control prevents fertiliser over-spill beyond field borders and waterways. This maximises input efficiency, protects sensitive areas, and ensures every kilogram yields maximum return.



HYDRAULIC DRAWBAR SUSPENSION

Integrated hydraulic suspension dampens heavy shocks between tractor and machine. This protects structural integrity, smooths high-speed paddock transport, and reduces wear and operator fatigue.



OVERSIZED GEARBOX, DRIVESHAFT & HYDRAULICS

Heavy-duty driveline components easily handle high torque and dense materials. This delivers maximum operational reliability, handles bigger payloads, and extends overall machine lifespan.

Inclusions & Options

		Inclusions ● Optional ○
TYRES	Range of Tractor and Floatation tyre options available. Contact your local Hansa Dealer for a full list.	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	○ ○
SECTION CONTROL	Single section Single conveyor - 10 linked section (ISOBUS Only) Twin conveyors - 14 sections (ISOBUS Only)	● ○ ○
AXLE	Single Series 150 ADR 10/335 (track options of 2,000mm - 3,000mm)	●
BIN CONSTRUCTION	2B 304 grade stainless steel	●
MUDGUARDS	Plastic radius mudguards	○
HYDRAULICS	Load Sense Open Centre PTO Power Pack	● ○ ○
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

SPREAD WIDTH
36m Urea, 18m Lime

VOLUME (WATER LEVEL)
11,450L

VOLUME (FERTILISER)
12,400L

VOLUME (LIME)
14,800L

TARE WEIGHT
4,650kg

UREA CAPACITY
9,300kg

LIME CAPACITY
14,000kg

LOADING HEIGHT
2,920mm

BIN LENGTH
4,500mm

OVERALL LENGTH
7,550mm

BIN WIDTH
2,300mm

AXLE TRACK
2,000mm - 3,000mm
(Depending on tyre size)

CONVEYOR WIDTH
725mm wide

CARRYING CAPACITY
14,000kg

OIL FLOW
150L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

HANSA PRECISION EQUIPMENT