T18 PRO SERIES




HANSA
PRECISION EQUIPMENT

T18 PRO SERIES


Built to take on larger jobs with ease, the Hansa T18 Pro Series brings higher capacity and heavy-duty performance directly to your operation. With premium features built in as standard, it delivers serious productivity, dependable coverage, and maximum value from day one.






STANDARD BOUNDARY CONTROL

Precision boundary control prevents fertiliser over-spill beyond field borders and waterways. This maximises input efficiency, protects sensitive areas, and ensures every kilogram yields maximum return.



HYDRAULIC DRAWBAR SUSPENSION

Integrated hydraulic suspension dampens heavy shocks between tractor and machine. This protects structural integrity, smooths high-speed paddock transport, and reduces wear and operator fatigue.



REAR STEERING AXLE

The rear steering axle tracks smoothly behind tractor wheels during sharp turns. This minimises crop damage, reduces soil compaction, and significantly lowers tyre wear.

Inclusions & Options

Inclusions ●
Optional ○

TYRES	Range of Tractor and Floatation tyre options available. Contact your local Hansa Dealer for a full list.	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H7 controller (7" Touch screen)	○ ○
SECTION CONTROL	Single section Single conveyor - 10 linked section (ISOBUS Only) Twin conveyors - 14 sections (ISOBUS Only)	● ○ ○
AXLE	Single Series 150 ADR 10/335 (track options of 2,000mm - 3,000mm)	●
BIN CONSTRUCTION	2B 304 grade stainless steel	●
MUDGUARDS	Plastic radius mudguards	○
HYDRAULICS	Load Sense Open Centre PTO Power Pack	● ○ ○
BRAKES	Hydraulic	●

A full range of options are available upon request

Specifications

SPREAD WIDTH
36m Urea, 18m Lime

VOLUME (WATER LEVEL)
12,750L

VOLUME (FERTILISER)
14,000L

VOLUME (LIME)
16,500L

TARE WEIGHT
6,050kg

UREA CAPACITY
10,500kg

LIME CAPACITY
18,000kg

LOADING HEIGHT
3,000mm
(may vary with tyre option)

BIN LENGTH
5,100mm

OVERALL LENGTH
8,150mm

BIN WIDTH
2,300mm

AXLE TRACK
2,000mm - 3,000mm
(Depending on tyre size)
Steer axle not available under 2,400mm

CONVEYOR WIDTH
725mm wide

CARRYING CAPACITY
18,000kg

OIL FLOW
150L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

HANSA PRECISION EQUIPMENT