# T24 PRO SERIES





HINNSA
PRECISION EQUIPMENT

# T24 PRO SERIES


Built for the toughest jobs and biggest acres, the Hansa T24 stands at the top of the Pro Series range. It pairs maximum payload capacity with a fully equipped standard specification, giving you non-stop productivity, heavy-duty durability, and complete reliability from day one.




### STANDARD BOUNDARY CONTROL

Precision boundary control prevents fertiliser over-spill beyond field borders and waterways. This maximises input efficiency, protects sensitive areas, and ensures every kilogram yields maximum return.



### HYDRAULIC DRAWBAR SUSPENSION

Integrated hydraulic suspension dampens heavy shocks between tractor and machine. This protects structural integrity, smooths high-speed paddock transport, and reduces wear and operator fatigue.



### REAR STEERING AXLE

The rear steering axle tracks smoothly behind tractor wheels during sharp turns. This minimises crop damage, reduces soil compaction, and significantly lowers tyre wear.

## Inclusions & Options

Inclusions ●
Optional ○

| | | |
|---|---|---|
| **TYRES** | Range of Tractor and Floatation tyre options available.<br>Contact your local Hansa Dealer for a full list. | ○ |
| **TARP** | 900 gsm rollover tarp | ○ |
| **LOAD CELLS** | When selected with ISOBUS rate controller auto rate control is enabled | ○ |
| **RATE CONTROLLER** | ISOBUS (auto rate calibration)<br>Hansa H7 controller (7" Touch screen) | ○<br>○ |
| **SECTION CONTROL** | Single section<br>Single conveyor - 10 linked section (ISOBUS Only)<br>Twin conveyors - 14 sections (ISOBUS Only) | ●<br>○<br>○ |
| **AXLE** | Single Series 150 ADR 10/335<br>(track options of 2,000mm - 3,000mm) | ● |
| **BIN CONSTRUCTION** | 2B 304 grade stainless steel | ● |
| **MUDGUARDS** | Plastic radius mudguards | ○ |
| **HYDRAULICS** | Load Sense<br>Open Centre<br>PTO Power Pack | ●<br>○<br>○ |
| **BRAKES** | Hydraulic | ● |

**A full range of options are available upon request**

## Specifications

**SPREAD WIDTH**
36m Urea, 18m Lime

**VOLUME (WATER LEVEL)**
18,000L

**VOLUME (FERTILISER)**
20,000L

**VOLUME (LIME)**
23,500L

**TARE WEIGHT**
6,850kg

**UREA CAPACITY**
15,000kg

**LIME CAPACITY**
24,000kg

**LOADING HEIGHT**
3,050mm
(may vary with tyre option)

**BIN LENGTH**
6,000mm

**OVERALL LENGTH**
9,050mm

**BIN WIDTH**
2,700mm

**AXLE TRACK**
2,000mm - 3,000mm
(Depending on tyre size)
Steer axle not available under 2,400mm

**CONVEYOR WIDTH**
725mm wide

**CARRYING CAPACITY**
24,000kg

**OIL FLOW**
160L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
**hansaequipment.com.au**

HANSA PRECISION EQUIPMENT