T7

PRIMARY SERIES




HANSA
PRECISION EQUIPMENT

T7 PRIMARY SERIES

Built with the same precision engineering as Hansa's Pro Series, the Primary Series focuses on core functionality without sacrificing durability. Purpose-built for small-scale farms and tasks requiring minimal soil impact, the T7 model delivers reliable, high-precision spreading with expanded payload capacity.





VARIABLE RATE TECHNOLOGY

Seamlessly maximise input efficiency using the Hansa H5 variable rate controller. Set your desired application rate, bout width and spinner speed directly from the cab, allowing precise rate control without the guesswork.



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T7 is built for ultimate durability. A grit blasted and 2 pack painted chassis protects against corrosion, ensuring long-term structural integrity and a premium finish.



OVER-SPECIFIED TYRES

Large, high profile floatation tyres easily handle heavy payloads while minimising soil compaction. This delivers superior stability across varying paddock conditions, extends tyre life, and enhances overall maneuverability.

Inclusions & Options

Inclusions ●
Optional ○

TYRES	Range of Tractor and Floatation tyre options available. Contact your local Hansa Dealer for a full list.	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H5 controller (5" Touch screen)	○ ○
AXLE	Single Series 80 BPW 8/285 (track options of 1,400mm - 3,000mm)	●
BIN CONSTRUCTION	2B 304 grade stainless steel	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

SPREAD WIDTH
30m Urea, 14m Lime

VOLUME (WATER LEVEL)
4,400L

VOLUME (FERTILISER)
5,000L

VOLUME (LIME)
5,800L

TARE WEIGHT
1,950kg

UREA CAPACITY
3,750kg

LIME CAPACITY
7,000kg

LOADING HEIGHT
2,150mm

BIN LENGTH
3,000mm

OVERALL LENGTH
5,480mm

BIN WIDTH
2,000mm

AXLE TRACK
1,400mm - 3,000mm
(Depending on tyre size)

CONVEYOR WIDTH
725mm wide

CARRYING CAPACITY
7,000kg

OIL FLOW
90L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

HANSA PRECISION EQUIPMENT