T9

PRIMARY SERIES




HANSA
PRECISION EQUIPMENT

T9 PRIMARY SERIES


The T9 combines a high-capacity bin with an impressive 36m spread pattern and iconic Hansa longevity. It maximises your value by streamlining core performance and stripping out premium extras like boundary control and hydraulic drawbar suspension featured on the Pro Series.





VARIABLE RATE TECHNOLOGY

Seamlessly maximise input efficiency using the Hansa H5 variable rate controller. Set your desired application rate, bout width and spinner speed directly from the cab, allowing precise rate control without the guesswork.



BUILT FOR DURABILITY

Manufactured from 304 stainless steel, the T9 is built for ultimate durability. A grit blasted and 2 pack painted chassis protects against corrosion, ensuring long-term structural integrity and a premium finish.



UPGRADED HYDRAULIC MOTORS

Heavy-duty hydraulic motors deliver high-flow power to maintain precise application rates at faster ground speeds. This ensures consistent coverage, maximises field efficiency, and reduces operating time without sacrificing accuracy.

Inclusions & Options

Inclusions ●
Optional ○

TYRES	Range of Tractor and Floatation tyre options available. Contact your local Hansa Dealer for a full list.	○
TARP	900 gsm rollover tarp	○
LOAD CELLS	When selected with ISOBUS rate controller auto rate control is enabled	○
RATE CONTROLLER	ISOBUS (auto rate calibration) Hansa H5 controller (5" Touch screen) Hansa H7 controller (7" Touch screen)	○ ○ ○
AXLE	Single Series 100 ADR 10/335 (track options of 1,400mm - 3,000mm)	●
BIN CONSTRUCTION	2B 304 grade stainless steel	●
BRAKES	Hydraulic	○

A full range of options are available upon request

Specifications

SPREAD WIDTH
36m Urea, 18m Lime

VOLUME (WATER LEVEL)
7,200L

VOLUME (FERTILISER)
8,000L

VOLUME (LIME)
9,400L

TARE WEIGHT
2,450kg

UREA CAPACITY
6,000kg

LIME CAPACITY
10,000kg

LOADING HEIGHT
2,350mm

BIN LENGTH
3,800mm

OVERALL LENGTH
6,980mm

BIN WIDTH
2,300mm

AXLE TRACK
1,400mm - 3,000mm
(Depending on tyre size)

CONVEYOR WIDTH
725mm wide

CARRYING CAPACITY
10,000kg

OIL FLOW
95L/min

Hansa provides all information in good faith, and reserves all rights to alter/change specifications without notice. Purchasers must conduct their own enquiries to ensure that the products are suitable for their own particular purposes as all information is provided as an approximation and are to be used as a guide only. Photographs may show aftermarket or optional equipment that is available at extra cost. Hansa Precision Equipment Pty Ltd. Copyright 2026. ABN: 74 604 073 350

139 Learmonth St, Alfredton VIC
sales@hansaequipment.com.au
hansaequipment.com.au

HANSA PRECISION EQUIPMENT